

Tehničke karakteristike artikla: WST2020150

Nazidni metalni orman, 1 vrata, IP66, 200x200x155 mm

čelični lim, RAL7035, s pocinčanom montažnom pločom, brava s dvostrukim zaključavanjem



SCHRACK info

- Material: Solid, cross-shaped construction, which is folded and welded from a cold-pressed sheet steel plate regardless of the size of the enclosure.
- The enclosure consists of two parts: Body and door.
- The door is secured by hinges and has an opening angle of 130°. The door is mounted using safety pins and the hinges are hidden. The door hinge can be changed easily from right to left. The doors have a foamed polyurethane seal.
- Mounting plate: Galvanised sheet steel, 2mm, folded on all sides. The mounting plate folded on all sides is mounted on welded M8 bolts on the rear of the enclosure and can be removed for mounting and wiring. The mounting plate is made of 2mm sendzimir galvanized sheet steel to comply with EMC guidelines. It has earthing points to establish a connection to the enclosure body.
- Protection class: Maximum protection for the devices is guaranteed due to the high degree of protection and impact resistance IK10 according to IEC 60529 standards. Corrosion protection for additional drilling should be considered.
- Mounting: The enclosure is mounted to the wall with screws (with plastic washers inside) directly with the rear wall or with a mounting kit (accessory WSTWB004 / WSTWB006), in both cases the IP degree of protection is maintained. The small opening radius of the doors makes it easy to mount enclosures directly next to each other.
- Delivery includes: Complete enclosure with gasket and screws, keys DIN 5mm and mounting plate incl. mounting material. Grounding possibilities are given.

IP65

IK10

Tehnički podaci

Neto širina (mm)	200,00
Neto visina (mm)	200,00
Neto dubina (mm)	155,00
Neto težina (kg)	2,83
Min. temperatura okoline (°C)	-20
Maks. temperatura okoline (°C)	70
Tip	Zidni orman od čeličnog lima
Visina (mm)	200
Širina (mm)	200
Dubina (mm)	155
Maksimalno opterećenje (kg)	80
Debljina stijenke tijela (mm)	1,2
IP stepen zaštite	IP65
Montažna ploča	Galvanizovani čelični lim 2mm
Opteretivost montažne ploče (kg)	55
Debljina montažne ploče (mm)	2
Visina montažne ploče (mm)	140
Širina montažne ploče (mm)	150
Broj vrata	1
Opteretivost vrata (kg)	20
Broj prirubnica	-
Debljina stijenke vrata (mm)	1,20
Ojačanje vrata	Ne
Brava	1
Šarke	2
Pričvršćenje stražnje ploče	4
Opis boje	RAL 7035 (svetlo siva)
Gubitak snage (W)	-30,00
Klasa zaštite	I

Tehnički crtež sa dimenzijama




Tabela artikla

OPIS	Kat. broj
Nazidni metalni orman, 1 vrata, IP66, 200x200x155 mm čelični lim, RAL7035, s pocinčanom montažnom pločom, brava s dvostrukim zaključavanjem	WST2020150
Dodatni pribor	
Set(4kom) za montažu WT ormara na zid pakiranje = 4 komada	WSTWB004
Pletenica za uzemljenje ormara dužine 260mm	WSTCUF260
Kablovski uvođnici, 28mm, za 6 kablova (1 pak. = 10 kom.) 3x 3,4mm, 3x 5-9mm	WSTCEG2806
Kablovski uvođnici, 40mm, za 10 kablova (1 pak. = 10 kom.) 3x 5-14mm, 7x 2-7mm	WSTCEG4010
Kablovske uvođnice 50mm, 8 perforiranih rupa (1 pak=5kom) kabelski uvođi: 2x 3-7mm, 1x 12-21mm, 1x 7-15mm, 4x 4-10mm	WSTCEG5008
Kablovski uvođnici, 50mm, za 7 kablova (1 pak. = 5 kom.) 7x 6-13mm	WSTCEG5007
Zatvara se sa 5mm dvostrukim uloškom za WST pripadajući ključ = DV903532	WSTL3532
Cilindar brava za WST ormara	WSSL3844-A
Polu-cilindrični umetak 5333, isti ključ za pomeranje ručice mit 1x Schlüssel 5333	DV905333