

Tehničke karakteristike artikla: XC1608911 -

Koaks.kabl RG-6, LSOH, 2-struki omotač, 90dB, 75ohm, Eca, 100m

Class A, beli, serija DIGI-SAT 3000



SCHRACK info

To guarantee high-quality, noise-free transmission of the high frequencies (from approx. 950 to 2150 MHz) from the LNB via multiswitch and SAT wall outlet to the SAT receiver it is necessary to use high-grade coax cables. Our high-frequency cables owe their top quality to their top-of-the-line components, cutting-edge production technology and the number of their shielding layers.



Tehnički podaci

Klasa	Klasa A
Unutrašnji provodnik	1,02 CCS
Izolacioni prečnik	4,60 Cell PE
Spoljni provodnik	Aluminijum poliester film
Pletenica	0,12 Al x 16 x 7
Pokrov pletenice (%)	75
Efikasnost zaštite (dB)	95
Prečnik (mm)	6,60
Spoljni omotač kabla	LSOH

Tehnički podaci - nastavak

Euroclass u skladu sa EN50575	Eca
Boja plašta	Bela
Min. radius savijanja (mm)	60
Nominalna težina (kg/km)	45
Otpor (Ohm)	75 ± 3
DC otpor na 20° C (Ohm/100m)	2,20
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	70
Dužina/pakovanje	100m - špulna
Kapacitet	52 ± 4 pF/m
Neto dužina (mm)	1.000,00
Neto prečnik (mm)	6,60
Neto težina (kg)	0,05

TIPIČNE VRIJEDNOSTI

Nominalno prigušenje:	
50 MHz	3.30dB / 100m
100 MHz	5.40dB / 100m
200 MHz	7.90dB / 100m
300 MHz	9.70dB / 100m
470 MHz	12.70dB / 100m
860 MHz	18.30dB / 100m
1000 MHz	20.20dB / 100m
1350 MHz	24.10dB / 100m
1750 MHz	28.60dB / 100m
2050 MHz	30.50dB / 100m
2250 MHz	32.10dB / 100m
2400 MHz	33.30dB / 100m
Gubici zbog povratnog signala:	
5 - 1.000 MHz	more than 30dB
1.000 - 2.000 MHz	more than 24dB
2.000 - 3.000 MHz	more than 20dB

Tabela artikla

OPIS	Kat. broj
Koaks.kabl RG-6,LS0H,2-struki omotač,90dB,75ohm,Eca,100m Class A, beli, serija DIGI-SAT 3000	XC1608911
Dodatni pribor	
Koaksijalni F-konektor,kompresioni,za 3000,3030,3040,3050 za koaksijalne kablove serije DIGI-SAT 3000,3030,3040,3050	XC16004983
Alat za kompresiju (montažu) koaksijalnih F-konektora "klešta za krimpovanje"	XC1600720
Alat za skidanje izolacije koaksijalnog kabla 6.6-6.8 i 11 mm za koaksijalne kablove prečnika 6.6-6.8mm i 11 mm	XC1600710
SAT Završna utičnica SAT/TV/RADIO,Class A,80x80mm,bela RAL 9010 (čisto bela), sa okvirom 80x80mm i nazidnom kutijom	HSATD3M
SAT Završna utičnica 2xSAT/TV/RADIO,Class A,80x80mm,bela RAL 9010 (čisto bela), sa okvirom 80x80mm i nazidnom kutijom	HSATD4M
Antenska završna utičnica 2-struka, 4 - 1.000MHz, 2 dB uključen okvir 80x80mm i N/Ž kućište, RAL9010	HSBKD2M